

INFINITY

BATTERY

IT75-12

RECHARGEABLE SEALED LEAD ACID (VRLA) BATTERY

Nominal Voltage **12 Volt**
 20 Hour Rate Capacity **75 Ah**



Dimensions	Inches	mm
Length	10.24	260
Width	6.69	170
Case Height	7.95	202
Terminal Height	8.07	205

Weight (Approx.)	Lbs.	Kg
	53.61	24.37

Constant Current Discharge Characteristics at 73.4°F (23°C)

Discharge Time	Discharge Amperes	Capacity in Ah's	Final Voltage	Discharge C-Rate
20.0 Hrs	3.7	75.00	10.50	0.05
9.2 Hrs	7.5	70.00	10.50	0.10
5.0 Hrs	12.7	63.75	10.20	0.17
4.1 Hrs	16.9	61.50	10.20	0.20
2.1 Hrs	26	55.10	9.94	0.35
64.0 Mins	45	48.00	9.54	0.6
32.5 Mins	75	40.63	9.60	1.0
7.2 Mins	225	27.00	6.00	3.0

Case Material A.B.S. (UL94-HB)

Terminal SCREW IN TERMINAL (M6)

Maximum Short Duration Discharge Current	
(5 Seconds or Less)	900 Amperes
(10 Seconds or Less)	600 Amperes
(60 Seconds or Less)	360 Amperes


Internal Resistance (Fully Charged Battery)
 (Approximately) 6.8 mOhm

Energy Density (@ 20 Hour Rate)
 1.72 Watt-Hours/Cubic Inch (105.2 Watt-Hours/Litre)

Specific Energy (@ 20 Hour Rate)
 17.8 Watt-Hours / Pound (39.24 Watt-Hours / Kg)

Operating Temperature Range	
Discharge	5°F (-15°C) ~ 122°F (50°C)
Recharge	32°F (0°C) ~ 104°F (40°C)
Storage	32°F (0°C) ~ 104°F (40°C)

Self Discharge Rate
 About 3% / Month @ 68~77°F (20~25°C)



Recharge Method : Connect battery to a Current Limited, Constant Voltage Source.

- Limit the Initial Recharge Current to 15 Amperes or less.
- To promote satisfactory performance in Cyclic Applications, an initial Recharge Current of 7.5 Amperes is recommended.
- Employ Charge Voltage Temperature Compensation when Battery Temperature is less than 50°F (10°C) or greater than 86°F (30°C). Use the **Recommended** Voltage and Normalize to 68°F (20°C).
- The use of Compensation through the whole Temperature range is not generally necessary, but doing so may optimize Service Life.
- If the **Recommended** Recharge voltage is used, no Temperature Compensation is required within the range of 50~86°F (10~30°C).

Cyclic Application Recharge Voltage (68°F / 20°C)

Minimum	Recommended	Maximum	Volts D.C. Per Cell
14.40	14.55	14.70	
2.40	2.425	2.45	

Temperature Coefficient: -2.8mV / °F / Cell (- 5mV / °C / Cell)

Standby Application Recharge Voltage (68°F / 20°C)

Minimum	Recommended	Maximum	Volts D.C. Per Cell
13.50	13.65	13.80	
2.25	2.275	2.30	

Temperature Coefficient: -1.7mV / °F / Cell (- 3mV / °C / Cell)